

PACKAGING MATERIAL DATA SHEET

General Data

Supplier and Manufacturer: SARONG S.p.a.

Reference Name: ALU/PE

Colours: Metallic grey

Application fields: Forming in Pharmaceutical, Cosmetic and Industrial applications

Products and Specifications

**Materials composed by Tempered Aluminium foil
laminated with PE (Low density Polyethylene)**

Thickness (μm)	Composition	Basis Weight (gr/m^2)	Lamination process	PE type
70	ALU 45 μm + PE 25 μm (not peelable)	144	Lamination by glue	Not peelable
85	ALU 45 μm + PE 40 μm (peelable)	158	Lamination by glue	Peelable
73	ALU 47 μm + PE 26 μm (not peelable)	153	Extrusion coating (compatible with phenolic products)	Not peelable

* Approximate data calculated from unofficial sources

Reel features

Inner core \varnothing : 70/76 mm • Ext. reel \varnothing : 300÷500 mm • Reel width: from 50 to 1100 mm

Printing

Printing by Rotogravure in one or two colours

Automatic packaging machines

Main uses: suppository forming/filling/hot sealing machines, the PE layer can peelable (peel-off opening of the packaging) or not peelable (opening by breaking in pre-cut area).



SARONG SpA – 42046 Reggiolo (RE) – Italy – Via C. Colombo, 18
Tel. +39 0522 212511 - Fax +39 0522
www.sarong.it - e-mail: info@sarong.it



USA DISTRIBUTOR:

Key International, Inc.
4 Corporate Drive, Cranbury, NJ 08512
P: 609-619-3685 F: 609-619-3686
Email: sales@keyinternational.com
Web: www.keyinternational.com